(43) International Publication Date

21 October 2004 (21.10.2004)

International Bureau

PCT

(10) International Publication Number WO 2004/089605 A1

(51) International Patent Classification7: 47/90 // B29L 23:00, B29K 101/12

B29C 55/26,

(21) International Application Number:

PCT/AU2004/000460

(22) International Filing Date: 8 April 2004 (08.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003901596

8 April 2003 (08.04.2003) AU


- (71) Applicants (for all designated States except US): VINIDEX PTY LIMITED [AU/AU]; 19-21 Loyalty Road, North Rocks, New South Wales 2151 (AU). UP-ONOR INNOVATION AB [SE/SE]; Industrivagen, S-513 18 Fristad (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): CHAPMAN, Peter, Glanville [AU/AU]; 45 Ronald Avenue, Greenwich, New South Wales 2065 (AU). HENWOOD, James, Victor

[AU/AU]; 9 Kariboo Close, Mona Vale, New South Wales 2103 (AU). MACOVAZ, George [AU/AU]; 16 Myson Drive, Cherrybrook, New South Wales 2120 (AU). JAR-VENKYLA, Jyri [FI/FI]; Tapiontie 4, FIN-SF-15780 Hollola (FI).

- (74) Agents: DAVIDSON, Geoffrey, Robert et al.; 1 Market Street, Sydney, New South Wales 2000 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR CONTROL OF PLASTICS TUBE ORIENTATION PROCESS



(57) Abstract: A continuous process for producing oriented plastic tube is disclosed having the steps of extrusion (12) of a tube to an initial extruded diameter, temperature conditioning (18), diametrical expansion (20) and cooling (30), characterised by control of the circumferential draw ratio by the step of adjusting the diameter of the extruded tube to an adjusted diameter by means of a variable diameter calibrator (13) located between said extrusion and temperature conditioning steps. A process line for carrying out the invention is also disclosed. Further embodiments of the invention include adjustment of the extruded wall thickness and compensatory adjustment of the adjusted diameter so as to effect a change in final wall thickness with unchanged draw ratio, a process for changing final product diameter and a start-up procedure for the process.

WO 2004/089605 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.